

SKID POWER - Especificaciones técnicas



Description

SKID POWER ha sido desarrollado para las minicargadoras (skid steer) que se utilizan en la construcción. Presenta una excelente tracción, así como elevadas propiedades de auto limpieza. Este neumático se caracteriza para la banda de rodadura extra profunda y una particular protección de los flancos, asegurando una excelente resistencia a los cortes y los desgarres, así como una extraordinaria duración. SKID POWER es el neumático ideal para las superficies terrosas.

UM

US Standard

Construction

 BIAS

Machinery

Industrial: Minicargadora compacta

Version	IMPLEMENT
Type	TL
Tyre Size	10 - 16.5
LI/SS	116 A8

Dimensions US Standard

Usa code	94055661
Ply Rating	8
Section Width (inch)	10
Overall Diameter (inch)	30.5
Static Loaded Radius (inch)	14
Rolling Circumference (inch)	90
Rim Rec	8.25
ECE	E11-106R-003534

Load capacity (lbs)

mph / psi	60
25	2755

Printed on 23/04/2024 15:15

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..