

SM 54 M IND-4S - Especificaciones técnicas



Description

SM 54 M IND-4S es una versión modificada del modelo SM 54. El perfil más plano de la banda de rodadura se manifiesta en una zona de contacto más amplia y asegura un largo ciclo de vida del neumático. Este neumático ha sido proyectado especialmente para las máquinas que se utilizan en la manipulación de los contenedores vacíos y para las grúas reach stacker utilizadas en las operaciones intermodales y logísticas. SM 54 M se caracteriza por una elevada estabilidad en la modalidad de levantamiento, así como por el profundo dibujo liso de la banda de rodadura que garantiza una excelente resistencia a los cortes.

UM

US Standard

Construction

 BIAS

Machinery

Industrial: Grúa Reach Stacker

Version	PORT INDUSTRIAL
Type	TL
Tyre Size	18.00 - 33

Dimensions US Standard

Usa code	94050215
Ply Rating	40
Overall Width (inch)	21.1
Overall Diameter (inch)	74.6
Static Loaded Radius (inch)	33.1
Rolling Circumference (inch)	220.8
Rim Rec	13.00/2.5
TRA Code	IND-4S

Load capacity (lbs)

mph / psi	145
5	59525

Printed on 29/04/2024 23:15

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..