

SNOW - RIDE (B) - Especificaciones técnicas



Description

SNOW-RIDE es específicamente idóneo para las operaciones que se realizan en la carretera en condiciones invernales con palas cargadoras y excavadoras. Este neumático se caracteriza para una excelente tracción y es ideal para los trabajos realizados en la nieve y el hielo. El dibujo especial de la banda de rodadura elimina los riesgos de derrape.

UM

International Standard

Construction

 BIAS

Machinery

Industrial: Buldócer • Pala cargadora

| | |
|-----------|-----------|
| Version | STANDARD |
| Type | TL |
| Tyre Size | 20.5 - 25 |

Dimensions International Standard

| | |
|----------------------------|-----------|
| Ply Rating | 16 |
| Section Width (mm) | 537 |
| Overall Diameter (mm) | 1492 |
| Static Loaded Radius (mm) | 652 |
| Rolling Circumference (mm) | 4423 |
| Rim Rec | 17.00/2.0 |
| Rim Alt | 17.00/1.7 |
| TRA Code | L2 |

Load capacity (Kg)

| | |
|------------|------|
| km/h / bar | 3.50 |
| 10 | 8250 |

Printed on 26/04/2024 18:47

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..