

SNOW - RIDE (B) - Especificaciones técnicas



Description

SNOW-RIDE es específicamente idóneo para las operaciones que se realizan en la carretera en condiciones invernales con palas cargadoras y excavadoras. Este neumático se caracteriza para una excelente tracción y es ideal para los trabajos realizados en la nieve y el hielo. El dibujo especial de la banda de rodadura elimina los riesgos de derrape.

UM

US Standard

Construction

❖ BIAS

Machinery

Industrial: Buldócer • Pala cargadora

Version	STANDARD
Type	TL
Tyre Size	20.5 - 25

Dimensions US Standard

Usa code	94044399
Ply Rating	16
Section Width (inch)	21.1
Overall Diameter (inch)	58.7
Static Loaded Radius (inch)	25.7
Rolling Circumference (inch)	174.1
Rim Rec	17.00/2.0
Rim Alt	17.00/1.7
TRA Code	L2

Load capacity (lbs)

mph / psi	51
5	18200

Printed on 26/04/2024 22:55

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..