

## SR 713 - Especificaciones técnicas



### Description

SR 713 es un neumático radial **All Steel** con tecnología VF para maquinaria agrícola. Este neumático se caracteriza por una robusta carcasa con cinturones de acero multicapa y por una banda de rodadura con un dibujo de ranuras múltiples que garantizan una baja resistencia al rodamiento, además del desgaste uniforme de la banda de rodadura. Gracias a una huella más ancha, este neumático VF asegura una reducida compactación del suelo. SR 713 se distingue tanto en términos de prestaciones como por su fiabilidad, ofreciendo óptimos niveles de velocidad incluso por carretera.

### UM

US Standard

### Construction

 RADIAL

### Machinery

Agricultura: Maquinaria agrícola

Version	STANDARD
Type	TL
Tyre Size	VF 245/70 R 19.5
LI/SS	142 D

## Dimensions US Standard

Usa code	94067732
Overall Width (inch)	9.6
Overall Diameter (inch)	33.2
Static Loaded Radius (inch)	14.7
Rolling Circumference (inch)	100.7
Rim Rec	7.50
ECE	E11-106R-006978
TRA Code	I1

## Load capacity (lbs)

mph / psi	75
40	5840

Printed on 05/12/2023 2:27

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..