

STAR TRAC - Especificaciones técnicas



Description

Star Trac es el neumático BKT para las cosechadoras que se utilizan en las plantaciones de algodón ya que pueden soportar cargas muy pesadas. Gracias al dibujo de la banda de rodadura específicamente profundo, este neumático asegura una excelente tracción en el terreno, así como óptimas prestaciones durante los desplazamientos por carretera. En las plantaciones de algodón que muestran los típicos arbustos de medias dimensiones, las operaciones de recogida requieren que el neumático esté caracterizado por óptimas capacidades de flotación, así como por una reducida compactación del suelo. Además, este neumático ha sido realizado con una mezcla especial que proporciona una elevada resistencia contra los cortes y los daños típicos de estos trabajos.

UM

International Standard

Construction

 BIAS

Machinery

Agricultura: Cosechadora de algodón

Version	STANDARD
Type	TL
Tyre Size	DW 500/95 D 32
LI/SS	162 A8/169 A5

Dimensions International Standard

Section Width (mm)	500
Overall Diameter (mm)	1836
Static Loaded Radius (mm)	809
Rolling Circumference (mm)	5324
Rim Rec	13.00 DW

Load capacity (Kg)

km/h / bar	1.70
40	4750
25	5800

Printed on 24/04/2024 20:34

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..