

## STEER GRIP - Especificaciones técnicas



### Description

STEER GRIP es el equipamiento ideal para los ejes de dirección de los camiones con volquete. Su ancha nervadura central y tacos lineales hace que este neumático sea idóneo para las aplicaciones free rolling (rodadura libre), garantizando excelentes prestaciones en condiciones mojadas y secas fuera de la carretera. La especial mezcla de la banda de rodadura ha sido realizada para combinar una óptima resistencia al desgaste con una buena resistencia a los cortes y los desgarros, mientras que su robusta carcasa asegura un prolongado ciclo de vida del neumático.

### UM

US Standard

### Construction

 BIAS

### Machinery

OTR: Volquete

Version	STANDARD
Type	TT
Tyre Size	11.00 - 20

## Dimensions US Standard

Usa code	94052103
Ply Rating	18
Overall Width (inch)	11.8
Overall Diameter (inch)	44.1
Static Loaded Radius (inch)	20.7
Rolling Circumference (inch)	133.7
Rim Rec	8.0
Rim Alt	7.5

## Load capacity (lbs)

mph / psi	110
55 LS/LD	6610

Printed on 23/04/2024 2:50

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..