

## SUPER GRADER - Especificaciones técnicas



### Description

SUPER GRADER (G-2) es un neumático diagonal específicamente desarrollado para las motoniveladoras. Presenta una excelente tracción y óptimas propiedades de auto limpieza. SUPER GRADER ha sido realizado con una mezcla especial que permite un ciclo de vida prolongado del neumático y se puede utilizar en los trabajos más pesados.

### UM

US Standard

### Construction

 BIAS

### Machinery

OTR: Motoniveladora

|           |            |
|-----------|------------|
| Version   | STANDARD   |
| Type      | TL         |
| Tyre Size | 16.00 - 24 |

## Dimensions US Standard

|                              |              |
|------------------------------|--------------|
| Usa code                     | 94035441     |
| Ply Rating                   | 16           |
| Overall Width (inch)         | 16.9         |
| Overall Diameter (inch)      | 57.1         |
| Static Loaded Radius (inch)  | 25.4         |
| Rolling Circumference (inch) | 169.6        |
| Rim Rec                      | 10.00 VA SDC |
| TRA Code                     | G2           |

## Load capacity (lbs)

|           |      |
|-----------|------|
| mph / psi | 44   |
| 25        | 9900 |

Printed on 27/04/2024 9:07

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..