

SUPER TRAX HD - Especificaciones técnicas



Description

SUPER TRAX HD ha sido específicamente proyectado para las carretillas elevadoras que se utilizan en la manipulación de material en las operaciones de trabajo pesado, incluidas las aplicaciones portuarias e mineras. La banda de rodadura extra profunda está realizada con una mezcla especial, resistente al desgaste, asegurando una larga vida operativa. SUPER TRAX HD se caracteriza por una robusta carcasa y el flanco reforzado del neumático traduciéndose en una excelente estabilidad e maniobrabilidad en la modalidad de levantamiento. El especial borde de protección de la llanta protege el neumático en el área de la pestaña de la llanta contra desinflamientos y daños.

UM

US Standard

Construction

 BIAS

Machinery

Industrial: Carretilla elevadora

Version	STANDARD
Type	TT
Tyre Size	8.15 - 15 (28 X 9 - 15)

Dimensions US Standard

Usa code	94056552
Ply Rating	14
Section Width (inch)	8.7
Overall Diameter (inch)	28.1
Static Loaded Radius (inch)	13.1
Rolling Circumference (inch)	85.4
Rim Rec	7.00
Rim Alt	7 BD

Load capacity (lbs)

mph / psi	145
15 LOAD WHEEL	8600
15 STEER WHEEL	6615
5 OTHER VEHICLES	8600
15 OTHER VEHICLES	6615
STATIC SIDE LOADER	9985

Printed on 27/04/2024 8:19

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..