

## SURE TRAX HD - Especificaciones técnicas



### Description

SURE TRAX HD es un neumático diagonal específicamente desarrollado para las motoniveladoras. Presenta una excelente tracción y óptimas propiedades de auto limpieza. SURE TRAX HD ha sido realizado con una mezcla especial que permite un ciclo de vida prolongado del neumático y se puede utilizar en los trabajos más pesados.

### UM

International Standard

### Construction

 BIAS

### Machinery

Industrial: Minicargadora compacta

Version	INDUSTRIAL
Type	TL
Tyre Size	33 X 15.5 - 16.5
LI/SS	151 A2

## Dimensions International Standard

Ply Rating	14
Section Width (mm)	400
Overall Diameter (mm)	855
Rim Rec	13.00
ECE	E11-106R-006012

## Load capacity (Kg)

	km/h / bar	4.80
	10	3450
	15	2725
	25	2520

Printed on 25/04/2024 20:36

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..