

TF 8181 - Especificaciones técnicas



Description

TF 8181 es un neumático que se utiliza tanto en el campo como en la carretera para los tractores 2WD/2RM empleados en los trabajos del campo y de transporte. Este neumático asegura un excelente comportamiento de la dirección.

UM

US Standard

Construction

 BIAS

Machinery

Agricultura: Tractor 2WD

Industrial: Remolque

| | |
|-----------|-----------|
| Version | STANDARD |
| Type | TT |
| Tyre Size | 6.00 - 16 |
| LI/SS | 91 A8 |

Dimensions US Standard

| | |
|------------------------------|-----------------------|
| Usa code | 94020591 |
| Ply Rating | 8 |
| Section Width (inch) | 6.8 |
| Overall Diameter (inch) | 29.3 |
| Static Loaded Radius (inch) | 13.8 |
| Rolling Circumference (inch) | 87.4 |
| Rim Rec | 4.50 E |
| Rim Alt | 4.00 E ; 5 K ; 5.00 F |
| ECE | E4-106R-002186 |
| TRA Code | F2 |

Load capacity (lbs)

| | |
|-----------|------|
| mph / psi | 68 |
| 25 | 1360 |

Printed on 20/04/2024 6:13

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..