

## TF 8181 - Especificaciones técnicas



### Description

TF 8181 es un neumático que se utiliza tanto en el campo como en la carretera para los tractores 2WD/2RM empleados en los trabajos del campo y de transporte. Este neumático asegura un excelente comportamiento de la dirección.

### UM

International Standard

### Construction

 BIAS

### Machinery

Agricultura: Tractor 2WD

Industrial: Remolque

Version	SPECIAL
Type	TT
Tyre Size	7.50 - 16
LI/SS	103 A6

## Dimensions International Standard

Ply Rating	8
Section Width (mm)	205
Overall Diameter (mm)	820
Static Loaded Radius (mm)	383
Rolling Circumference (mm)	2445
Rim Rec	5.50 F
Rim Alt	5.00 F ; 5 K ; 6.00 F
ECE	E11-106R-004413
TRA Code	F2

## Load capacity (Kg)

km/h / bar	3.70
30	875

Printed on 20/04/2024 6:19

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..