

TF 9090 - Especificaciones técnicas



Description

TF 9090 es un neumático que se utiliza para los minitractores empleados en los trabajos del campo. El especial diseño de la banda de rodadura ofrece un excelente comportamiento de la dirección en suelos sueltos.

UM

US Standard

Construction

 BIAS

Machinery

Agricultura: Minitractor
Industrial: Remolque

Version	STANDARD
Type	TT
Tyre Size	4.00 - 16
LI/SS	61 A8

Dimensions US Standard

Usa code	94034680
Ply Rating	4
Section Width (inch)	4.4
Overall Diameter (inch)	24.8
Static Loaded Radius (inch)	11.9
Rolling Circumference (inch)	73.9
Rim Rec	3.00 D
ECE	E4-106R-002183
TRA Code	F2

Load capacity (lbs)

mph / psi	50
25	570

Printed on 03/12/2023 10:51

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..