

## TF 9090 - Especificaciones técnicas



### Description

TF 9090 es un neumático que se utiliza para los minitractores empleados en los trabajos del campo. El especial diseño de la banda de rodadura ofrece un excelente comportamiento de la dirección en suelos sueltos.

### UM

US Standard

### Construction

 BIAS

### Machinery

Agricultura: Minitractor  
Industrial: Remolque

Version	STANDARD
Type	TT
Tyre Size	5.50 - 16
LI/SS	82 A8

## Dimensions US Standard

Usa code	94020874
Ply Rating	6
Section Width (inch)	5.9
Overall Diameter (inch)	28
Static Loaded Radius (inch)	13.1
Rolling Circumference (inch)	83.3
Rim Rec	4.00 E
Rim Alt	3.50 D ; 4.50 E
ECE	E4-106R-001955
TRA Code	F2

## Load capacity (lbs)

	mph / psi	56
	25	1050

Printed on 02/12/2023 19:08

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..