

TR 117 - Especificaciones técnicas



Description

TR 117 es ideal para las operaciones de riego con pivote central. El especial dibujo de la banda de rodadura se traduce en una excelente tracción y extraordinarias propiedades de autolimpieza.

UM

US Standard

Construction

 BIAS

Machinery

Agricultura: Equipo de riego a pivote

Version	STANDARD
Type	TL
Tyre Size	14.9 - 24
LI/SS	109 A8

Dimensions US Standard

Usa code	94029051
Ply Rating	4
Section Width (inch)	14.9
Overall Diameter (inch)	49
Static Loaded Radius (inch)	22.6
Rolling Circumference (inch)	144.1
Rim Rec	W 13
Rim Alt	W 11 ; W 12
ECE	E4-106R-002026
TRA Code	R1

Load capacity (lbs)

mph / psi	12	16
25	2270	---
CREEP	---	4795

* - CREEP SPEED - 200 FT/30 MIN (61 M/30 MIN)

Printed on 26/04/2024 20:12

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..