

## TR 128 - Especificaciones técnicas



### Description

TR 128 ha sido particularmente proyectado para tractores compactos y cultivadores rotativos. El amplio y profundo diseño de los tacos y la mezcla particularmente resistente a los cortes asegura una vida prolongada del neumático. TR 128 se distingue por la máxima tracción en los terrenos húmedos.

### UM

International Standard

### Construction

 BIAS

### Machinery

Agricultura: Cultivador rotativo • Vehículo universal

Version	STANDARD
Type	TT
Tyre Size	5 - 12

## Dimensions International Standard

Ply Rating	4
Section Width (mm)	127
Overall Diameter (mm)	554
Static Loaded Radius (mm)	262
Rolling Circumference (mm)	1700
Rim Rec	4 JA
ECE	E11-106R-003477

## Load capacity (Kg)

km/h / bar	2.40
30	220

Printed on 25/04/2024 18:34

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..