

TR 135 - Especificaciones técnicas



Description

TR 135 es idóneo para tractores en los trabajos del campo. La carcasa reforzada y la mezcla particularmente resistente a los cortes y los desgarres proporcionan un ciclo de vida más largo. Sus óptimas prestaciones de tracción, auto limpieza y estabilidad, son las características clave que hacen que TR 135 sea el neumático ideal, incluso en las condiciones más difíciles del terreno.

UM

US Standard

Construction

 BIAS

Machinery

Agricultura: Tractor
Industrial: Remolque

Version	STANDARD
Type	TT
Tyre Size	12.4 - 24
LI/SS	124 A8

Dimensions US Standard

Usa code	94003150
Ply Rating	12
Section Width (inch)	12.4
Overall Diameter (inch)	45.7
Static Loaded Radius (inch)	21.4
Rolling Circumference (inch)	140.7
Rim Rec	W 11
Rim Alt	W 9 ; W 10
ECE	E4-106R-002040
TRA Code	R1

Load capacity (lbs)

mph / psi	48
25	3520

Printed on 17/04/2024 4:05

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..