

## TR 135 - Especificaciones técnicas



### Description

TR 135 es idóneo para tractores en los trabajos del campo. La carcasa reforzada y la mezcla particularmente resistente a los cortes y los desgarres proporcionan un ciclo de vida más largo. Sus óptimas prestaciones de tracción, auto limpieza y estabilidad, son las características clave que hacen que TR 135 sea el neumático ideal, incluso en las condiciones más difíciles del terreno.

### UM

International Standard

### Construction

 BIAS

### Machinery

Agricultura: Tractor  
Industrial: Remolque

|           |              |
|-----------|--------------|
| Version   | DUAL BEAD HD |
| Type      | TL           |
| Tyre Size | 20.8 - 42    |
| LI/SS     | 168 A6       |

## Dimensions International Standard

|                            |                 |
|----------------------------|-----------------|
| Ply Rating                 | 18              |
| Section Width (mm)         | 535             |
| Overall Diameter (mm)      | 1950            |
| Static Loaded Radius (mm)  | 909             |
| Rolling Circumference (mm) | 5733            |
| Rim Rec                    | W 18 L          |
| Rim Alt                    | W 16 L          |
| ECE                        | E11-106R-005853 |
| TRA Code                   | R1              |

## Load capacity (Kg)

| km/h / bar | 3.20 |
|------------|------|
| 30         | 5600 |

Printed on 17/04/2024 4:47

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..