

TR 136 - Especificaciones técnicas



Description

TR 136 ha sido desarrollado por BKT para los tractores y los remolques que se utilizan en los trabajos del campo y de transporte. Este neumático asegura una tracción superior en cualquier condición de trabajo, así como una óptima resistencia a cualquier tipo de corte, reduciendo los tiempos de parada de la máquina e incrementando la productividad. Gracias a el número aumentado de los tacos, TR 136 asegura excelente tracción incluso a cargas elevadas.

UM

US Standard

Construction

 BIAS

Machinery

Agricultura: Tractor • Remolque

| | |
|-----------|------------------------|
| Version | STANDARD |
| Type | TT |
| Tyre Size | 16.9 - 30 (14 - 30) |
| LI/SS | 143 A8 |

Dimensions US Standard

| | |
|------------------------------|-----------------|
| Usa code | 94044108 |
| Ply Rating | 14 |
| Section Width (inch) | 16.9 |
| Overall Diameter (inch) | 58.5 |
| Static Loaded Radius (inch) | 26.7 |
| Rolling Circumference (inch) | 175.4 |
| Rim Rec | W 15 L |
| Rim Alt | W 14 L |
| ECE | E11-106R-005243 |
| TRA Code | R1 |

Load capacity (lbs)

| | |
|-----------|------|
| mph / psi | 40 |
| 25 | 6000 |

Printed on 26/04/2024 10:52

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..