

TR 137 - Especificaciones técnicas



Description

TR 137 es el neumático ideal para todas las operaciones de recogida, ya que asegura una excelente tracción en el campo incluso a cargas elevadas. Este neumático está disponible en diferentes versiones: la versión "aramid-belted", con cinturones de aramida, garantiza una mejor resistencia a la perforación y protección contra los daños típicos de esta actividad; la versión "HD" ofrece una extraordinaria resistencia a los cortes y los desgarres, así como un ciclo de vida más largo.

UM

International Standard

Construction

✦ BIAS

Machinery

Agricultura: Cosechadora

Version	STANDARD
Type	TL
Tyre Size	30.5L - 32
LI/SS	167 A6

Dimensions International Standard

Ply Rating	16
Section Width (mm)	770
Overall Diameter (mm)	1865
Static Loaded Radius (mm)	831
Rolling Circumference (mm)	5520
Rim Rec	DH 27 B
Rim Alt	DW 27 B
ECE	E4-106R-002282
TRA Code	R1

Load capacity (Kg)

km/h / bar	1.80
30	5450

Printed on 20/04/2024 7:01

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..