

TR 138 - Especificaciones técnicas



Description

TR 138 ha sido particularmente proyectado para los elevadores telescópicos y las cargadoras retroexcavadoras. Este neumático es idóneo para la preparación de suelo y las aplicaciones de pulverización. Una tracción superior, auto limpieza y estabilidad, son las características clave que hacen que TR 138 sea el neumático ideal, incluso en las condiciones más difíciles del terreno.

UM

US Standard

Construction

 BIAS

Machinery

Agricultura: Cargadora retroexcavadora • Elevador telescópico

| | |
|-----------|------------|
| Version | STANDARD |
| Type | TL |
| Tyre Size | 17.5L - 24 |
| LI/SS | 151 A8 |

Dimensions US Standard

| | |
|------------------------------|-----------------|
| Usa code | 94061877 |
| Ply Rating | 12 |
| Section Width (inch) | 17.7 |
| Overall Diameter (inch) | 50.8 |
| Static Loaded Radius (inch) | 22.7 |
| Rolling Circumference (inch) | 151 |
| Rim Rec | DW 15L |
| Rim Alt | DW 14L |
| ECE | E11-106R-005232 |

Load capacity (lbs)

| | |
|-----------|------|
| mph / psi | 25 |
| 39 | 7605 |

Printed on 26/04/2024 11:22

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..