

## TR 144 - Especificaciones técnicas



### Description

TR 144 es idóneo para los minitractores que se utilizan en los trabajos del campo. TR 144 garantiza extraordinarias prestaciones en cualquier condición de trabajo que requiera una excelente tracción con cargas elevadas. TR 144 también está disponible en una versión "special", idónea para las operaciones de trabajo más pesadas.

### UM

US Standard

### Construction

 BIAS

### Machinery

Agricultura: Minitractor

Version	HD
Type	TT
Tyre Size	8 - 16
LI/SS	88 A8

## Dimensions US Standard

Usa code	94048373
Ply Rating	6
TMPH	1
Section Width (inch)	7.9
Overall Diameter (inch)	30.9
Static Loaded Radius (inch)	14.1
Rolling Circumference (inch)	92.2
Rim Rec	6 L ; 6 LB ; 6.00 F
ECE	E11-106R-004087
TRA Code	R1

## Load capacity (lbs)

mph / psi	28
25	1235

Printed on 20/04/2024 5:05

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..