

## TR 145 - Especificaciones técnicas



### Description

TR 145 ha sido especialmente desarrollado para los tractores pequeños. El particular dibujo de la banda de rodadura ofrece una excelente tracción, así como extraordinarias propiedades de auto limpieza. El amplio y profundo diseño de los tacos asegura una vida prolongada del neumático. TR 145 presenta una amplia área de contacto que proporciona un excelente confort de guía y buena estabilidad direccional.

### UM

US Standard

### Construction

 BIAS

### Machinery

Agricultura: Minitractor

Version	STANDARD
Type	TT
Tyre Size	160/90 - 12
LI/SS	72 A8

## Dimensions US Standard

Usa code	94062744
Ply Rating	6
Section Width (inch)	6.3
Overall Diameter (inch)	24.8
Static Loaded Radius (inch)	11.6
Rolling Circumference (inch)	77.5
Rim Rec	4.00
ECE	E11-106R-005854
TRA Code	R1

## Load capacity (lbs)

mph / psi	36
2	785

Printed on 25/04/2024 22:07

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..