

## TR 171 - Especificaciones técnicas



### Description

TR 171 es un neumático con una banda de rodadura profunda, idóneo para los tractores que se utilizan en los trabajos del campo. Gracias a las extraordinarias propiedades de auto limpieza, este neumático es ideal para utilizarlo en los terrenos húmedos y mojados. Realizado con una mezcla especial, TR 171 garantiza una excelente tracción y durabilidad, incluso en las condiciones de trabajo más duras.

### UM

US Standard

### Construction

 BIAS

### Machinery

Agricultura: Tractor

Version	STANDARD
Type	TT
Tyre Size	11.2 - 24
LI/SS	113 A8

## Dimensions US Standard

Usa code	94029792
Ply Rating	8
Section Width (inch)	11.2
Overall Diameter (inch)	43.5
Static Loaded Radius (inch)	20.4
Rolling Circumference (inch)	134
Rim Rec	W 10
Rim Alt	W 9
ECE	E11-106R-004098
TRA Code	R1W+

## Load capacity (lbs)

mph / psi	36
25	2540

Printed on 23/04/2024 13:41

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..