

## TR 171 - Especificaciones técnicas



### Description

TR 171 es un neumático con una banda de rodadura profunda, idóneo para los tractores que se utilizan en los trabajos del campo. Gracias a las extraordinarias propiedades de auto limpieza, este neumático es ideal para utilizarlo en los terrenos húmedos y mojados. Realizado con una mezcla especial, TR 171 garantiza una excelente tracción y durabilidad, incluso en las condiciones de trabajo más duras.

### UM

International Standard

### Construction

 BIAS

### Machinery

Agricultura: Tractor

|           |           |
|-----------|-----------|
| Version   | STANDARD  |
| Type      | TT        |
| Tyre Size | 14.9 - 24 |
| LI/SS     | 128 A6    |

## Dimensions International Standard

|                            |                |
|----------------------------|----------------|
| Ply Rating                 | 8              |
| Section Width (mm)         | 391            |
| Overall Diameter (mm)      | 1265           |
| Static Loaded Radius (mm)  | 575            |
| Rolling Circumference (mm) | 3792           |
| SRI (mm)                   | 600            |
| Rim Rec                    | W 13           |
| Rim Alt                    | W 11 ; W 12    |
| ECE                        | E4-106R-002742 |
| TRA Code                   | R1W+           |

## Load capacity (Kg)

|            |      |
|------------|------|
| km/h / bar | 1.80 |
| 30         | 1800 |

Printed on 23/04/2024 14:35

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..