

## TR 173 - Especificaciones técnicas



### Description

TR 173 es un neumático para los tractores idóneo para condiciones mojadas y lo arrozales. El particular dibujo de la banda de rodadura ofrece óptimas características de auto limpieza, así como una reducida compactación del terreno gracias a su amplia área de contacto.

### UM

International Standard

### Construction

 BIAS

### Machinery

Agricultura: Tractor

Version	STANDARD
Type	TT
Tyre Size	12.4 - 24
LI/SS	115 A6

## Dimensions International Standard

Ply Rating	6
Section Width (mm)	315
Overall Diameter (mm)	1160
Static Loaded Radius (mm)	541
Rolling Circumference (mm)	3509
SRI (mm)	550
Rim Rec	W 11
Rim Alt	W 9 ; W 10
ECE	E11-106R-004480
TRA Code	R1W

## Load capacity (Kg)

km/h / bar	1.70
30	1215

Printed on 26/04/2024 20:16

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..