TR 270 - Especificaciones técnicas

Description

TR 270 es un neumático para tractores, idóneo para utilizarlo en las labores del campo. Este neumático ha sido especialmente proyectado para ofrecer las máximas prestaciones en terrenos húmedos y mojados. En estas condiciones del terreno, a un neumático se le requiere que ofrezca un agarre superior, así como elevadas propiedades de auto limpieza. TR 270 satisface perfectamente todas estas características.

UM

International Standard

Construction

BIAS

Machinery

Agricultura: Tractor

Version	STANDARD
Type	TT
Tyre Size	23.1 - 30
LI/SS	146 A6

Dimensions International Standard

Ply Rating	8
Section Width (mm)	590
Overall Diameter (mm)	1748
Static Loaded Radius (mm)	790
Rolling Circumference (mm)	5227
Rim Rec	DW 20 A ; DW 20 B
TRA Code	R2

Load capacity (Kg)

km/h / bar	1.10
30	3000

Printed on 16/04/2024 10:45

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..