

TR 313 - Especificaciones técnicas



Description

TR 313 es un neumático para el césped y la jardinería, idóneo para las operaciones en los segmentos de municipalidad/mantenimiento y para utilizarlo en las labores del campo con la maquinaria agrícola, las zanjadoras y las máquinas para la recogida de fruta. Su amplia área de contacto garantiza un excelente agarre. El neumático TR 313 ha sido proyectado para garantizar un elevado nivel de estabilidad incluso en las condiciones de trabajo más críticas, así como óptimas propiedades de auto-limpieza.

UM

US Standard

Construction

 BIAS

Machinery

Agricultura: Maquinaria agrícola • Máquina para la recogida de fruta • Zanjadora

Version	STANDARD
Type	TL
Tyre Size	31 X 15.50 - 15

Dimensions US Standard

Usa code	94025589
Ply Rating	8
Section Width (inch)	14.6
Overall Diameter (inch)	30.7
Static Loaded Radius (inch)	13.5
Rolling Circumference (inch)	87.9
Rim Rec	13 LB
ECE	E4-106R-002208

Load capacity (lbs)

mph / psi	45
30	2760

Printed on 19/04/2024 3:38

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..