

## TR 315 - Especificaciones técnicas



### Description

TR 315 es un neumático para el césped y la jardinería, idóneo para las operaciones en los segmentos de municipalidad/mantenimiento. Este neumático es ideal para utilizarlo con la maquinaria agrícola, las zanjadoras y las máquinas para la recogida de fruta. TR 315 presenta una amplia área de contacto que proporciona un excelente agarre, así como una extraordinaria estabilidad en cualquier condición y óptimas propiedades de auto-limpieza.

### UM

International Standard

### Construction

 BIAS

### Machinery

Agricultura: Maquinaria agrícola • Máquina para la recogida de fruta • Zanjadora

Version	SPECIAL
Type	TL
Tyre Size	26 X 12.00 - 12

## Dimensions International Standard

Ply Rating	10
Section Width (mm)	308
Overall Diameter (mm)	655
Static Loaded Radius (mm)	289
Rolling Circumference (mm)	1905
Rim Rec	10½ JA
Rim Alt	8½ JA ; 9½ JA
ECE	E11-106R-004519

## Load capacity (Kg)

km/h / bar	3.80
15	1450

Printed on 26/04/2024 4:22

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..