

## TR 319 - Especificaciones técnicas



### Description

TR 319 es un neumático que se utiliza en la maquinaria agrícola, como en las máquinas para la recogida de fruta y las zanjadoras destinadas tanto a los trabajos de jardinería como del campo y en los segmentos de municipalidad/mantenimiento. Este neumático muestra una amplia área de contacto que se traduce en una óptima tracción. Por tanto, TR 319 es idóneo para usarlo en superficies tanto mojadas, cuando se requiere estabilidad y propiedades de auto-limpieza.

### UM

International Standard

### Construction

 BIAS

### Machinery

Agricultura: Maquinaria agrícola • Máquina para la recogida de fruta • Zanjadora

|           |                 |
|-----------|-----------------|
| Version   | STANDARD        |
| Type      | TL              |
| Tyre Size | 26 X 12.00 - 12 |
| LI/SS     | 116 A3          |

## Dimensions International Standard

|                            |                          |
|----------------------------|--------------------------|
| Ply Rating                 | 8                        |
| Section Width (mm)         | 318                      |
| Overall Diameter (mm)      | 640                      |
| Static Loaded Radius (mm)  | 290                      |
| Rolling Circumference (mm) | 1908                     |
| Rim Rec                    | 10.50 AT                 |
| Rim Alt                    | 8.0 AT ; 8.5 AT ; 9.0 AT |
| ECE                        | E11-106R-003560          |

## Load capacity (Kg)

|            |      |
|------------|------|
| km/h / bar | 3.00 |
| 15         | 1250 |

Printed on 26/09/2023 18:15

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..