

## TR 387 - Especificaciones técnicas



### Description

TR 387 es un neumático agro-industrial, idóneo para los remolques que transportan la caña da azúcar y los compactadores. Este neumático se caracteriza por una elevada capacidad de carga y está disponible en diferentes versiones con el fin de satisfacer las exigencias específicas de los usuarios en términos de resistencia a los cortes y los desgarres, trabajos pesados y durabilidad. La versión "dual bead", de doble talón, es particularmente idónea para los tractores industriales y las operaciones de transporte con remolques.

### UM

US Standard

### Construction

 BIAS

### Machinery

Agricultura: Remolque

Industrial: Compactador

Version	HD
Type	TT
Tyre Size	18.4 - 30 (15 - 30)
LI/SS	147 A8

## Dimensions US Standard

Usa code	94005147
Ply Rating	14
Section Width (inch)	18.7
Overall Diameter (inch)	60.2
Static Loaded Radius (inch)	26.8
Rolling Circumference (inch)	173
Rim Rec	DW 16 L
Rim Alt	DW 15 L
TRA Code	R3

## Load capacity (lbs)

mph / psi	38
25	6780

Printed on 25/04/2024 20:33

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..