

TR 390 - Especificaciones técnicas



Description

TR 390 es un neumático agro-industrial, idóneo para las remolques que transportan la caña da azúcar y los compactadores. El neumático TR 390 se caracteriza por su elevada capacidad de carga y el aumento de la durabilidad. Su versión "dual bead HD", de doble talón HD, es particularmente idónea para los tractores industriales y las operaciones de transporte con remolques, mientras que la versión "dual bead HD special", de doble talón HD especial, es ideal para los trabajos más pesados.

UM

International Standard

Construction

❖ BIAS

Machinery

Agricultura: Remolque
Industrial: Compactador

| | |
|-----------|-----------|
| Version | STANDARD |
| Type | TL |
| Tyre Size | 23.1 - 26 |
| LI/SS | 153 A6 |

Dimensions International Standard

| | |
|----------------------------|----------------|
| Ply Rating | 12 |
| Section Width (mm) | 595 |
| Overall Diameter (mm) | 1560 |
| Static Loaded Radius (mm) | 690 |
| Rolling Circumference (mm) | 4545 |
| SRI (mm) | 750 |
| Rim Rec | DW 20 B |
| ECE | E4-106R-002317 |
| TRA Code | R3 |

Load capacity (Kg)

| km/h / bar | 1.70 |
|------------|------|
| 30 | 3650 |

Printed on 21/02/2024 6:33

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..