

## TR 391 - Especificaciones técnicas



### Description

TR 391 es un neumático agro-industrial, idóneo para las operaciones de transporte y compactación realizadas con remolques para la caña da azúcar y compactadores. TR 391 se caracteriza por su extraordinaria capacidad de carga y una vida operativa más larga.

### UM

International Standard

### Construction

 BIAS

### Machinery

Agricultura: Remolque

Industrial: Compactador

|           |           |
|-----------|-----------|
| Version   | STANDARD  |
| Type      | TL        |
| Tyre Size | 14.9 - 24 |
| LI/SS     | 128 A6    |

## Dimensions International Standard

|                            |                         |
|----------------------------|-------------------------|
| Ply Rating                 | 8                       |
| Section Width (mm)         | 405                     |
| Overall Diameter (mm)      | 1270                    |
| Static Loaded Radius (mm)  | 574                     |
| Rolling Circumference (mm) | 3805                    |
| SRI (mm)                   | 600                     |
| Rim Rec                    | DW 13                   |
| Rim Alt                    | DW 11 ; DW 12 ; DW 13 L |
| ECE                        | E11-106R-003365         |
| TRA Code                   | R3                      |

## Load capacity (Kg)

| km/h / bar | 1.80 |
|------------|------|
| 30         | 1800 |

Printed on 24/02/2024 6:31

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..