

## TR 391 - Especificaciones técnicas



### Description

TR 391 es un neumático agro-industrial, idóneo para las operaciones de transporte y compactación realizadas con remolques para la caña da azúcar y compactadores. TR 391 se caracteriza por su extraordinaria capacidad de carga y una vida operativa más larga.

### UM

US Standard

### Construction

 BIAS

### Machinery

Agricultura: Remolque

Industrial: Compactador

Version	STANDARD
Type	TL
Tyre Size	14.9 - 24
LI/SS	119 A8

## Dimensions US Standard

Usa code	94005260
Ply Rating	6
Section Width (inch)	15.9
Overall Diameter (inch)	50
Static Loaded Radius (inch)	22.6
Rolling Circumference (inch)	149.8
Rim Rec	DW 13
Rim Alt	DW 11 ; DW 13 L ; DW 12
TRA Code	R3

## Load capacity (lbs)

mph / psi	20
25	3000

Printed on 27/04/2024 17:57

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..