

TR 393 (B) - Especificaciones técnicas



Description

TR 393 (B) se ha diseñado especialmente para sembradoras, pulverizadores y maquinaria de aperos dentro y fuera de la carretera. El diseño especial de la banda de rodadura proporciona las mejores propiedades de flotación y autolimpieza, además de una larga vida útil. Gracias a su superficie de contacto grande, TR 393 (B) garantiza una excelente tracción y minimiza la compactación del suelo.

UM

International Standard

Construction

 BIAS

Machinery

Agricultura: Empacadora de heno • Maquinaria agrícola • Esparcidor

Version	STUBBLE RESISTANT
Type	TL
Tyre Size	31 X 13.50 - 15
LI/SS	124 B

Dimensions International Standard

Ply Rating	12
Section Width (mm)	350
Overall Diameter (mm)	777
Rim Rec	10 LB
ECE	E11-106R-008131
TRA Code	R3

Load capacity (Kg)

km/h / bar	5.20
50	1600

Printed on 28/04/2024 20:00

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..