

TR 459 - Especificaciones técnicas



Description

TR 459 ha sido específicamente proyectado para las operaciones de excavación y de carga, así como los trabajos realizados en el sector de la municipalidad y el mantenimiento con tractores y ternas. Este neumático ofrece una elevada estabilidad y está disponible en dos versiones. La versión "special" garantiza un ciclo de vida prolongado del neumático.

UM

International Standard

Construction

 BIAS

Machinery

Agricultura: Cargadora retroexcavadora • Tractor
Industrial: Cargadora retroexcavadora

Version	INDUSTRIAL
Type	TL
Tyre Size	21L - 28
LI/SS	157 A8

Dimensions International Standard

Ply Rating	12
Section Width (mm)	535
Overall Diameter (mm)	1480
Rim Rec	DW 18 A
ECE	E11-106R-005335
TRA Code	R4

Load capacity (Kg)

km/h / bar	2.20
40	4125

Printed on 18/04/2024 23:57

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..