

TR 461 - Especificaciones técnicas



Description

TR 461 es un neumático que BKT ha desarrollado para los trabajos realizados en la municipalidad y el mantenimiento con tractores, así como para las operaciones de carga con elevadores telescópicos. La protección del flanco se caracteriza por la particular resistencia a los cortes y las laceraciones que garantiza una vida más larga del neumático, incluso en superficies duras, además de una excelente estabilidad.

UM

US Standard

Construction

 BIAS

Machinery

Industrial: Cargadora retroexcavadora • Elevador telescópico • Tractor

| | |
|-----------|------------|
| Version | STANDARD |
| Type | TL |
| Tyre Size | 19.5L - 24 |
| LI/SS | 151 A8 |

Dimensions US Standard

| | |
|------------------------------|----------|
| Usa code | 94016761 |
| Ply Rating | 12 |
| Section Width (inch) | 19.3 |
| Overall Diameter (inch) | 51.6 |
| Static Loaded Radius (inch) | 22.8 |
| Rolling Circumference (inch) | 151.6 |
| Rim Rec | DW 16 L |
| TRA Code | R4 |

Load capacity (lbs)

| | |
|-----------|------|
| mph / psi | 34 |
| 25 | 7600 |

Printed on 25/04/2024 5:48

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..