

## TR 678 IND - Especificaciones técnicas



### Description

TR 678 IND ha sido particularmente desarrollado para las aplicaciones industriales. El robusto dibujo de los tacos garantiza una excelente tracción y auto-limpieza. La tenaz estructura de la carcasa se traduce en una elevada capacidad de carga, mientras que los cinturones de acero protegen el neumático contra los pinchazos y otros daños. TR 678 IND se caracteriza por una mezcla resistente a los cortes que garantiza, incluso en terrenos difíciles y en condiciones extremas, una excelente resistencia a los cortes y los desgarros.

### UM

International Standard

### Construction

 BIAS

### Machinery

Industrial: Pala excavadora • Remolque

|                    |               |
|--------------------|---------------|
| Version            | DUAL BEAD     |
| Type               | TL            |
| Tyre Size          | 600/40 - 22.5 |
| LI/SS DRIVE WHEEL  | 157 A8        |
| LI/SS FREE ROLLING | 169 A8        |

## Dimensions International Standard

|                            |                 |
|----------------------------|-----------------|
| Section Width (mm)         | 615             |
| Overall Diameter (mm)      | 1085            |
| Static Loaded Radius (mm)  | 483             |
| Rolling Circumference (mm) | 3264            |
| Rim Rec                    | AG 20.00        |
| ECE                        | E11-106R-006973 |

## Load capacity (Kg)

| km/h / bar | 4.10 |
|------------|------|
| 40 FR      | 5800 |
| 40 DW      | 4125 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 19/01/2025 22:03

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..