

TR 678 - Especificaciones técnicas



Description

TR 678 ha sido particularmente desarrollado para las aplicaciones forestales. El robusto dibujo de los tacos garantiza una excelente tracción y auto-limpieza. La tenaz estructura de la carcasa se traduce en una elevada capacidad de carga, mientras que los cinturones de acero protegen el neumático contra los pinchazos y otros daños. TR 678 se caracteriza por una mezcla resistente a los cortes que garantiza, incluso en terrenos difíciles y en condiciones extremas, una excelente resistencia a los cortes y las roturas.

UM

International Standard

Construction

❖ BIAS

Machinery

Agricultura: Maquinaria agrícola • Remolque
Industrial: Pala excavadora • Remolque

Version	STEEL BELTED
Type	TL
Tyre Size	600/65 - 34
LI/SS	166 A2 / 162 A6

Dimensions International Standard

Ply Rating	16
Section Width (mm)	610
Overall Diameter (mm)	1644
Static Loaded Radius (mm)	758
Rolling Circumference (mm)	4916
Rim Rec	DW 20 B
TRA Code	LS2

Load capacity (Kg)

km/h / bar	2.60
30	4750
10	5300

Printed on 20/04/2024 14:29

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..