

TR 882 - Especificaciones técnicas



Description

TR 882 es un neumático muy versátil que se utiliza en diferentes aplicaciones y máquinas. Ha sido proyectado para utilizarlo con maquinaria agrícola, máquinas para la recogida del heno/empacadoras y máquinas para las plantaciones de caña de azúcar. Desarrollado con una mezcla especial para reducir los daños, este neumático asegura durabilidad superior y excelente tracción en todas las condiciones en el campo. TR 882 también está disponible en las versiones "aramid-belted", "HD" y "special" para satisfacer las exigencias más específicas de los usuarios finales.

UM

International Standard

Construction

 BIAS

Machinery

Agricultura: Empacadora de heno • Cosechadora •
 Maquinaria agrícola • Remolque
 Industrial: Remolque

Version	STANDARD
Type	TL
Tyre Size	400/60 - 15.5
LI/SS DRIVE WHEEL	137 A8
LI/SS FREE ROLLING	149 A8

Dimensions International Standard

Ply Rating	18
Section Width (mm)	400
Overall Diameter (mm)	875
Static Loaded Radius (mm)	378
Rolling Circumference (mm)	2605
SRI (mm)	410
Rim Rec	AG 13.00
ECE	E4-106R-001878

Load capacity (Kg)

km/h / bar	4.50
10 FR	4550
25 FR	3870
30 FR	3640
40 FR	3250
10 DW	3220
25 DW	2735
30 DW	2575
40 DW	2300

Printed on 26/04/2024 22:16

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..