

TR 882 - Especificaciones técnicas



Description

TR 882 es un neumático muy versátil que se utiliza en diferentes aplicaciones y máquinas. Ha sido proyectado para utilizarlo con maquinaria agrícola, máquinas para la recogida del heno/empacadoras y máquinas para las plantaciones de caña de azúcar. Desarrollado con una mezcla especial para reducir los daños, este neumático asegura durabilidad superior y excelente tracción en todas las condiciones en el campo. TR 882 también está disponible en las versiones "aramid-belted", "HD" y "special" para satisfacer las exigencias más específicas de los usuarios finales.

UM

US Standard

Construction

 BIAS

Machinery

Agricultura: Empacadora de heno • Cosechadora •
 Maquinaria agrícola • Remolque
 Industrial: Remolque

Version	ARAMID BELTED HD
Type	TL
Tyre Size	400/60 - 15.5
LI/SS DRIVE WHEEL	137 A8
LI/SS FREE ROLLING	149 A8

Dimensions US Standard

Usa code	94048304
Ply Rating	18
Section Width (inch)	15.7
Overall Diameter (inch)	34.4
Static Loaded Radius (inch)	14.9
Rolling Circumference (inch)	102.6
Rim Rec	AG 13.00
ECE	E11-106R-005354

Load capacity (lbs)

mph / psi	65
5 FR	10030
15 FR	8530
20 FR	8020
25 FR	7160
5 DW	7100
15 DW	6030
20 DW	5680
25 DW	5070

Printed on 26/04/2024 18:12

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..