

TRAC FARM - Especificaciones técnicas



Description

TRAC FARM es un neumático para trabajos pesados, específicamente diseñado para los tractores en las aplicaciones de los trabajos del campo y de transporte. La banda de rodadura profunda y la mezcla resistente a los cortes y los desgarres hacen que este neumático sea idóneo para las condiciones de trabajo más difíciles, garantizando el mejor rendimiento de la inversión durante todo el ciclo de vida del producto. TRAC FARM ha sido diseñado con un número aumentado de los tacos asegurando excelente tracción y propiedades de auto-limpieza.

UM

US Standard

Construction

 BIAS

Machinery

Agricultura: Tractor

Version	STANDARD
Type	TT
Tyre Size	18.4 - 30
LI/SS	145 A8

Dimensions US Standard

Usa code	94042395
Ply Rating	12
Section Width (inch)	18.4
Overall Diameter (inch)	61
Static Loaded Radius (inch)	28.2
Rolling Circumference (inch)	179.4
Rim Rec	W 16 L
Rim Alt	W 15 L
ECE	E11-106R-003628
TRA Code	R1

Load capacity (lbs)

mph / psi	32
25	6400

Printed on 28/04/2024 5:00

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..