

TRAC SUPER - Especificaciones técnicas



Description

TRAC SUPER es el primer neumático radial introducido por BKT en el segmento de la municipalidad. La estructura del neumático con cinturones de acero asegura una óptima conducción lisa, combinada con las mejores prestaciones de tracción. Por tanto, este neumático es particularmente idóneo para trabajar en superficies de amplios prados, como en los parques y a lo largo de las carreteras.

UM

International Standard

Construction

 RADIAL

Machinery

Agricultura: Minitractor

Version	STANDARD
Type	TL
Tyre Size	440/50 R 17
LI/SS	135 D

Dimensions International Standard

Section Width (mm)	441
Overall Diameter (mm)	872
Static Loaded Radius (mm)	395
Rolling Circumference (mm)	2674
SRI (mm)	410
Rim Rec	14.00
Rim Alt	13.00
ECE	E4-106R-000662

Load capacity (Kg)

km/h / bar	0.8	1.0	1.2	1.6	2.0	2.4	2.8	3.2	3.6
65	955	960	1070	1265	1440	1635	1855	1985	2180
40	1300	1305	1455	1720	1960	2225	2525	2700	2965
30	1440	1450	1615	1915	2175	2475	2805	3000	3295
10	1720	1730	1925	2280	2595	2945	3340	3575	3925

Printed on 04/03/2024 12:13

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..