

## TUF LUG - Especificaciones técnicas



### Description

TUF LUG es idóneo para los remolques y las camionetas utilizadas para transportar. Este neumático ofrece una óptima tracción y una extraordinaria durabilidad, asegurando un prolongado ciclo de vida del producto.

### UM

International Standard

### Construction

 BIAS

### Machinery

Agricultura: Camión ligero • Remolque  
Industrial: Camión ligero • Remolque

|           |           |
|-----------|-----------|
| Version   | STANDARD  |
| Type      | TT        |
| Tyre Size | 7.50 - 16 |

### Dimensions International Standard

|                       |        |
|-----------------------|--------|
| Ply Rating            | 16     |
| Section Width (mm)    | 216    |
| Overall Diameter (mm) | 830    |
| Rim Rec               | 6.00 G |
| Rim Alt               | 5.50 F |

## Load capacity (Kg)

|            |      |
|------------|------|
| km/h / bar | 7.60 |
| 100 LS     | 1600 |
| 100 LD     | 1400 |

Printed on 19/04/2024 3:56

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..