

## VIJETA - Especificaciones técnicas



### Description

VIJETA es un neumático agrícola idóneo para utilizarlo por carretera y fuera de la carretera. El diseño de la banda de rodadura con nervadura de 5 costillas optimiza la distribución de la carga. Además, su mezcla resistente al desgaste y su robusta carcasa garantizan un largo ciclo de vida del neumático.

### UM

International Standard

### Construction

 BIAS

### Machinery

Agricultura: Remolque

Version	STANDARD
Type	TT
Tyre Size	7.00 - 19

## Dimensions International Standard

Ply Rating	10
Section Width (mm)	195
Overall Diameter (mm)	852
Rim Rec	5.00
ECE	E11-106R-004106

## Load capacity (Kg)

km/h / bar	5.15
15	1360

Printed on 25/04/2024 16:21

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..