

XL GRIP (BHL) - Especificaciones técnicas



Description

XL GRIP (BHL) ha sido particularmente desarrollado para las cargadoras retroexcavadoras que se utilizan en las operaciones más difíciles de excavación, apisonado y carga. El dibujo no direccional de la banda de rodadura asegura una óptima tracción y estabilidad. La mezcla especial de la banda de rodadura se traduce en una excelente resistencia a los cortes y las laceraciones, prolongando la vida de la banda de rodadura.

UM

US Standard

Construction

 BIAS

Machinery

Industrial: Cargadora retroexcavadora

Version	INDUSTRIAL
Type	TT
Tyre Size	16.9 - 28
LI/SS	152 A8

Dimensions US Standard

Usa code	94043873
Ply Rating	12
Overall Width (inch)	17.7
Overall Diameter (inch)	55.1
Static Loaded Radius (inch)	25.2
Rolling Circumference (inch)	164.4
Rim Rec	DW 15L
Rim Alt	DW 14L

Load capacity (lbs)

mph / psi	38
25	7830

Printed on 23/04/2024 5:48

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..