

## XL GRIP (E3) - Especificaciones técnicas



### Description

XL GRIP (E-3) es un neumático de telas cruzadas que se utiliza en los volquetes rígidos. Ha sido proyectado específicamente para minimizar el riesgo de cortes y perforaciones en condiciones que requieran una excepcional tracción y estas características se traducen en una vida más prolongada del neumático.

### UM

International Standard

### Construction

 BIAS

### Machinery

OTR: Dumper rígido

Version	STANDARD
Type	TT
Tyre Size	18.00 - 25

## Dimensions International Standard

Ply Rating	40
Overall Width (mm)	510
Overall Diameter (mm)	1615
Static Loaded Radius (mm)	739
Rolling Circumference (mm)	4780
Rim Rec	13.00/2.5
Rim Alt	15.00/2.5
TRA Code	E3/L3

## Load capacity (Kg)

km/h / bar	7.00	9.50
50	9750	-
10	-	17000

Printed on 20/04/2024 14:16

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..