

## XL GRIP (L3) - Ficha técnica



### Description

XL GRIP (E-3/L-3) es un neumático de telas cruzadas de base ancha (**wide**) desarrollado para palas cargadoras, que minimiza el riesgo de cortes y perforaciones en las operaciones de carga más pesadas. Este neumático asegura una excelente tracción, así como un ciclo de vida prolongado del producto.

### UM

US Standard

### Construction

 BIAS

### Machinery

Industrial: Pala cargadora

OTR: Buldócer • Pala cargadora

SIZE	Version	USACode	TRA Code	PR	RIM REC	RIM ALT	OW	OD	SLR	RC	Type
16.0/70 - 20	STANDARD	94030538	L3	16	13 SDC		15.9	42.9	18.9	129.7	TL
15.5 - 25	STANDARD	94051182	E3/L3	12	12.00/1.3	12.00/1.3 (DC)	15.8	50.6	22.6	148.3	TL
17.5 - 25	DUAL BEAD	94031351	E3/L3	20	14.00/1.5		17.1	53	24.5	156.7	TL
17.5 - 25	DUAL BEAD	94063406	E3/L3	24	14.00/1.5		17.1	53	24.5	156.7	TL
17.5 - 25	DUAL BEAD	94051830	E3/L3	20	14.00/1.5		17.1	53	24.5	156.7	TT
17.5 - 25	STANDARD	94040650	E3/L3	12	14.00/1.5		17.1	53	24.5	156.7	TL
17.5 - 25	STANDARD	94015719	E3/L3	16	14.00/1.5		17.1	53	24.5	156.7	TL
17.5 - 25	STANDARD	94015740	E3/L3	20	14.00/1.5		17.1	53	24.5	156.7	TL
20.5 - 25	STANDARD	94040667	E3/L3	12	17.00/2.0		20.9	58.5	26.9	173	TL
20.5 - 25	STANDARD	94015832	E3/L3	16	17.00/2.0		20.9	58.5	26.9	173	TL
20.5 - 25	STANDARD	94015856	E3/L3	20	17.00/2.0		20.9	58.5	26.9	173	TL
20.5 - 25	STANDARD	94032235	E3/L3	24	17.00/2.0		20.9	58.5	26.9	173	TL
23.5 - 25	ARAMID BELTED HD	94054107	E3/L3	24	19.50/2.5		23.6	64	29.2	189.4	TL
23.5 - 25	STANDARD	94015863	E3/L3	16	19.50/2.5		23.6	64	29.2	189.4	TL
23.5 - 25	STANDARD	94015870	E3/L3	20	19.50/2.5		23.6	64	29.2	189.4	TL
23.5 - 25	STANDARD	94015894	E3/L3	24	19.50/2.5		23.6	64	29.2	189.4	TL
26.5 - 25	STANDARD	94040674	L3	20	22.00/3.0		26.8	68.5	31.3	202.8	TL
26.5 - 25	STANDARD	94015900	L3	28	22.00/3.0		26.8	68.5	31.3	202.8	TL
26.5 - 25	STANDARD	94027989	L3	32	22.00/3.0		26.8	68.5	31.3	202.8	TL
29.5 - 25	STANDARD	94015917	L3	28	25.00/3.5		29.9	73.2	33.4	218.3	TL
29.5 - 25	STANDARD	94029594	L3	32	25.00/3.5		29.9	73.2	33.4	218.3	TL

Printed on 14/04/2024 16:17

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..