

## XL GRIP ULTRA - Especificaciones técnicas



### Description

XL GRIP ULTRA es un neumático de telas cruzadas proyectado para volquetes utilizados en condiciones de servicio pesado, como aplicaciones en la minería, en las conteras o en las obras de construcción. Este neumático se caracteriza por una robusta carcasa de nylon con juntas de conexión optimizadas así como una mezcla especial de la banda de rodadura para asegurar una elevada resistencia a los cortes y las laceraciones, durabilidad y resistencia al desgaste excelentes en combinación con extraordinarias propiedades de autolimpieza también en superficies rocosas.

### UM

US Standard

### Construction

 BIAS

### Machinery

OTR: Volquete

Version	STANDARD
Type	TT
Tyre Size	12.00 - 20

## Dimensions US Standard

Usa code	94069569
Ply Rating	20
Overall Width (inch)	12.6
Overall Diameter (inch)	45.5
Static Loaded Radius (inch)	21.5
Rolling Circumference (inch)	136.4
Rim Rec	8.5
Rim Alt	8.0

## Load capacity (lbs)

mph / psi	110
55 LS/LD	7610

Printed on 20/04/2024 14:39

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..