

TECHNICAL SPECIFICATION

Applications Small Tractor
 Description TR 126 is designed to fit small tractors in soil tillage operations and is particularly suitable on muddy ground. The deep lugs and the tread pattern provide excellent traction and outstanding self-cleaning features providing best tire performance in all operating conditions.

Pattern Name TR 126
 Version STANDARD
 US Code 94004539
 Type TT
 Tire Size 7 - 14
 LI/SS 72 A6
 PR 4



Dimensions (U/M US Standard)
 Section Width (in) 6.7
 Overall Diameter (in) 27.2
 Static Loaded Radius (in) 12.6
 Rolling Circumference (in) 81.5
 Rim Rec 5 JA ; 5 KB

LOAD CAPACITY TABLE (lbs)

mph / psi	24
20	785

* Tolerances: Overall Diameter ± 2% | Section Width ± 2% | Rolling Circumference ± 2.5%

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints.
 All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..